



Established 1954

Vipond's Paints Pty Ltd

2 Norris Street North Coburg 3058
Phone (03) 93504188 Fax (03) 93542732
Email vic@viponds.com.au

www.viponds.com.au

PRODUCT INFORMATION

[Back to Index](#)

GRAFFITI CLEANER

DESCRIPTION

A solvent based cleaner to aid in the removal of graffiti from Viponds Graffiti Proof.

Graffiti should be removed as soon as possible for two reasons. Firstly, it will discourage the Graffiti Artists and secondly, the graffiti will be easier to remove. Graffiti is normally applied with a spray can – acrylic lacquer or enamel and sometimes with a felt tip pen.

This cleaner is a solvent that will completely remove acrylic lacquers at anytime and easily remove enamel paints that are less than 24 hours old. Aged enamels are difficult to soften and removal may take some time. Constant use of this cleaner may eventually weaken the Viponds Graffiti Proof.

Graffiti from some felt tip pens can be easily removed with the cleaner, whilst other pens can leave a stain which is impossible to remove. This can only be removed by the removal of the Graffiti Proof Clear by peeling (when the Graffiti Proof is being used as a sacrificial coating) or eroding the surface with fine sandpaper or a scotch brite pad.

USE

Soak part of a soft cloth with the cleaner and rub onto the graffiti. Allow about 15 seconds for the cleaner to soften the graffiti then remove the graffiti with a dry cloth. Repeat this procedure until the graffiti is removed.

Try to rub the cleaner onto the graffiti and not onto the Graffiti Proof Clear. Constant rubbing with the presence of the solvent may eventually cause the Graffiti Clear to breakdown and the print will be spoilt.

ie Clean off the graffiti not the Graffiti Proof Clear!

SAFETY

This product is classified as hazardous. It is recommended to wear protective clothing, gloves and safety glasses. Refer to the material safety data sheet.

PACKAGING

Available in 1 and 4 litre metal cans

GRAFFITI CLEANER

Testing

The digital print market is continually changing, with new substrates and inks being offered on a regular basis. As the methods and conditions of application and use of this product are beyond control of Vipond's Paints Pty. Ltd. it is recommended that the customer tests the product thoroughly for their own particular application.

The main test is to check adhesion – Graffiti Proof forms a very tough film and if the adhesion is not satisfactory then the clear can delaminate from the substrate. This may be a desired property as it becomes a sacrificial coating.

It is also important to determine the best method of application and film thickness required to achieve the desired properties for the end application.

Call customer service (03) 93504188 for further information or for the location of your nearest stockist.

April 2005

[Back to Index](#)