

MATERIAL SAFETY DATA SHEET

[Back to Index](#)

Page 1 of 3

GRAFFITI CLEANER

Re issue April 2005

Classified as Hazardous according to Worksafe Australia

COMPANY DETAILS

Vipond's Paints Pty Ltd (A.C.N. 004 362 127) Tel: 03 93504188
2-4 Norris Street NORTH COBURG VIC 3058 Fax: 03 93542732

IDENTIFICATION

PRODUCT NAME: GRAFFITI CLEANER

UN Number: 1263

Dangerous Goods Class: 3

Hazchem Code: 3(Y)E

Packaging Group: II

Poisons Schedule: 6

Use: A solvent for cleaning graffiti off Viponds 2 part graffiti coating.

PHYSICAL DESCRIPTION AND OTHER PROPERTIES

Appearance: Clear liquid
Boiling Point: 56 to 170 degC.
Vapour Pressure: Greater than 1
Specific Gravity: 0.81
Flashpoint: -17 degC (closed cup)
Flammability Limits: Lel. 1.6 Uel. 10.9
Solubility in Water: Insoluble

INGREDIENTS

Chemical/Substance Name	CAS Number	Proportion
Hazardous Xylene	1330-20-7	75%

MATERIAL SAFETY DATA SHEET

GRAFFITI CLEANER

Page 2 of 3

HEALTH HAZARD INFORMATION

HEALTH EFFECTS - ACUTE

Swallowed May cause irritation to the mouth, throat, digestive tract and stomach. Aspiration into the lungs may cause pneumonitis.

Eye May cause irritation

Skin May cause irritation.

Inhalation May cause irritation to nose, throat and respiratory tract. May cause dizziness, nausea, headache and sleepiness.

HEALTH EFFECTS - CHRONIC

Prolonged inhalation of the vapour may result in nervous system effects such as dizziness, nausea, headache and sleepiness.

Prolonged or repeated exposure may cause defatting of the skin and may result in dermatitis.

FIRST AID

Swallowed If swallowed, **DO NOT** induce vomiting. If there is any suspicion of aspiration into the lungs obtain medical advice immediately.

Eye Wash with copious quantities of water for 15 minutes, holding eyelids apart. If irritation persists seek medical attention.

Skin Remove contaminated clothing and wash affected skin with soap and water.

Inhaled Move to fresh air, keep warm and rest. Seek medical attention if symptoms persist.

Advice to Doctor Treat symptomatically

PRECAUTIONS FOR USE

Exposure Standards TWA Xylene 80 ppm 350 gm/m³

Engineering Controls Provide adequate ventilation. Air circulation must be sufficient to prevent the likelihood of breathing the vapour.

Personal Protection Avoid contact with skin and eyes. Wear protective clothing and safety glasses. Avoid inhaling the vapour or mist. Observe good personal hygiene. Wear PVC, Nitrile or Neoprene gloves complying with AS 2161 is recommended.

Flammability Flammable liquid. Avoid heat, sparks and ignition sources.

MATERIAL SAFETY DATA SHEET

Page 3 of 3

GRAFFITI CLEANER

SAFE HANDLING INFORMATION

STORAGE AND TRANSPORT

Store in a cool area away from heat and any sources of ignition and in accordance with AS1940 – The Storage and Handling of Flammable and Combustible Liquids. Keep containers closed when not in use.

Transport according to class 3 (Flammable Liquid). Emergency procedure guide AS 1678.3C1.

SPILLS AND DISPOSAL

Remove all ignition sources and ventilate the area. Contain spill to prevent contamination of drains and waterways. Use absorbent material such as sand, earth, sawdust to collect and to transfer into sealed containers. Dispose of waste in accordance with the relevant regulations.

FIRE / EXPLOSION HAZARD

Flammable and will emit fumes. On heating, containers may rupture and explode.

Extinguish with foam, CO2 or dry chemical. Keep adjacent containers cool with water spray. When fighting the fire in enclosed areas wear self – contained breathing apparatus.

CONTACT

For further information contact Alan Vipond 03 93504188

The information herein is, to the best of our knowledge, correct and complete. It is meant to describe safety requirements of our products and should not be construed as guaranteeing specific properties. No warranty express or implied is made as to its accuracy, reliability or completeness.

[Back to Index](#)